

Overview

The IcoQube™ is a first-class packaging solution for intercontinental transport. It comes in four foldable sizes specifically designed to maximise sea container capacity, therefore increasing component volume delivery and saving transport costs.

The IcoQube helps to protect the environment by reducing the number of shipments resulting in reduced carbon emissions.

The IcoQube has a four-way access system for forklift trucks, two folding lids for simple filling and emptying and is RFID compatible.

The IcoQube helps you achieve greater supply chain efficiencies with CHEP's pooling network to save time, money and the hassle of managing oneway packaging of containers.



Features and Benefits

- Achieve greater transport and storage efficiencies with 4-way entry design
- Realise improved operational efficiency as all containers are RFID compatible
- Reduce transport costs with containers available in 4 sizes and all designed to maximise sea container capacity
- Decrease occupational health and safety risk to the labour force – all containers are made from strong and lightweight material
- Minimise storage costs with a best-in-class foldable ratio of 9:5:1
- Reduce physical waste and disposal costs compared to one way packaging – all containers are moisture resistant, reusable and environmentally friendly
- Increase product protection during transport with dual latching lids
- Easily identify contents with label placard on all four sides of the sleeve
- Ensure greater stability with all components (lid, sleeve, pallet) interlocking

Specifications

Dimensions - in millimetres

	Length	Width	Height
External	1150	975	1107
Internal	1112.6	937.6	918

Nominal Capacity and Weight

Maximum capacity	0.96 m3
Maximum load weight	400 kgs
Tare weight	29.3 kgs

Configuration and Stacking

Stacked layers in transit	2
Stacked layers for storage	3
Return Ratio	9.5

40' high cube sea container can hold 48 units when loaded, and 456 units when empty

Notes

Materials

Colour - CHEP Blue Pallet, Lid and Sleeve

CHEP Code

14450